



Data sheet

Simply better IROC® SR for Pitched Roofs

The IROC® SR rail system is suitable for corrugated roofs, tile roofs, standing seam roofs, and Kalzip roofs. With its cross-bracing design, IROC® SR is perfect for portrait and landscape mounting. The module clips are already fully pre-assembled and can be attached anywhere along the long side of the module, ensuring complete flexibility during installation.

The roof hook connection can be made from the front.

Advantages:

- ✓ Structurally proven components
- ✓ Fast assembly
- ✓ Minimal use of materials
- ✓ Suitable for all module types
- ✓ Cross mounting possible
- ✓ Module clips already pre-assembled
- ✓ Profile standard lengths 4.880 mm and 2.440 mm
- ✓ Can be used for span lengths up to 2.40 meters

Mounting type	Roof parallel
Profile length	Standard: 4.880 mm and 2.440 mm
Module size	For all common module types, also suitable for unframed modules
Module orientation	Portrait and landscape mounting
Roof covering	Pantiled roof, corrugated sheet roof, standing seam roof, Kalzip roof
Material	Aluminum, screw connections and roof anchors V2A
Connection	Roof hooks, hanger bolts, Kalzip clamp, sheet metal seam clamp
Requirements	The load-bearing capacity of the roof and the roof insulation must be checked and guaranteed by the customer.

